

PratiKa industrial socket - 63 A - 3P + N + E - 380...415 V AC - IP67

81283

Main

| Range | Mureva |
|---------------------------|---------------|
| Product or component type | Socket |
| Device short name | Mureva socket |
| Plug, socket category | Low voltage |
| Poles description | 3P + N + E |
| Network type | AC |
| Outlet standard | Industrial |

Complementary

| Mounting mode | Panel-mounted | |
|-------------------------------------|---|--|
| Plug, socket, control station shape | Angled | |
| [In] rated current | 63 A | |
| [Ue] rated operational voltage | 380415 V | |
| Network frequency | 50/60 Hz | |
| Ground lug clockwise position | 6 h | |
| Plug, socket material | Housing: self-extinguishing engineering polymer | |
| Contacts material | Pins: stainless steel Sleeves: nickel plated brass Springs: stainless steel | |
| Connections - terminals | Captive screws, completely loosened | |
| Cable cross section | 625 mm² | |
| Net weight | 0.52 kg | |
| Base dimension | 100 x 107 mm | |
| Height | 107 mm | |
| width | 100 mm | |
| Depth | 129 mm | |
| Colour | Grey (RAL 7035) | |
| Voltage colour | Red | |

Environment

| Standards | EN 60309-1 EN 60309-2 | |
|-------------------------|------------------------------|--|
| IP degree of protection | IP67 conforming to IEC 60529 | |

| IK degree of protection | IK08 conforming to EN 62262 | |
|---------------------------------------|---|--|
| Fire resistance | 850 °C conforming to IEC 60695-2-11 | |
| Relative humidity | 50 % at 40 °C 70 % at 30 °C 90 % at 20 °C | |
| Ambient air temperature for operation | 35 °C (86400 s) | |

Packing Units

| PCE |
|----------|
| 1 |
| 11.8 cm |
| 12.0 cm |
| 12.9 cm |
| 530.0 g |
| S03 |
| 15 |
| 30.0 cm |
| 30.0 cm |
| 40.0 cm |
| 8.437 kg |
| |

Contractual warranty

Warranty 18 months

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

How this information helps you >

| ⊘ Environmental footprint | |
|---|-------------------------------|
| Carbon footprint (kg.eq.CO2 per CR, Total Life cycle) | 50 |
| Environmental Disclosure | Product Environmental Profile |

Use Better

| Packaging made with recycled cardboard | No | |
|--|--|--|
| Packaging without single use plastic | No | |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) | |
| SCIP Number | 89350e0d-a4ac-4516-bf86- fdaed8a227fc | |
| REACh Regulation | REACh Declaration | |
| China RoHS Regulation | China RoHS declaration | |

Use Again

| ○ Repack and remanufacture | |
|----------------------------|--|
| Circularity Profile | No need of specific recycling operations |

Take-back

No