

Product datasheet

Specifications



Acti 9 - PK P&S - single door - 32A - 5 pin

A9HKS532

Main

Range	Acti9
Product name	PK P&S Units
Product or component type	Consumer unit
Device application	Power socket distribution
Colour	White (RAL 9003)

Complementary

Product compatibility	PK panel-mounted straight socket
Enclosure mounting	Surface Flush
[In] rated current	32 A
Pin number	5
Total number of 18 mm modules	4
Enclosure/cubicle description	Single door enclosure
Enclosure material	Galvanized steel box Galvanized steel DIN rail Galvanized steel cable gland plate CRCA front plate
Height	External: 305 mm
Width	External: 138 mm
Depth	External : 65 mm

Environment

IP degree of protection	IP30
IK degree of protection	IK08
Standards	IS 8623-1 IS 8623-3 IEC 61439-3
Product certifications	CPRI ERDA

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7 cm

Package 1 Width	31 cm
Package 1 Length	14.2 cm
Package 1 Weight	1.97 kg

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[How this information helps you >](#)

Environmental footprint

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	42
---	----

Environmental Disclosure

[Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard	Yes
--	-----

Packaging without single use plastic	No
--------------------------------------	----

EU RoHS Directive	Compliant with Exemptions
-------------------	---------------------------

REACH Regulation	REACH Declaration
------------------	-----------------------------------

China RoHS Regulation	China RoHS declaration
-----------------------	--

Use Again

Repack and remanufacture

Circularity Profile	No need of specific recycling operations
---------------------	--

Take-back	No
-----------	----