

Product datasheet

Specifications



Acti 9 - PSG DB - double door - IP43 - 6 ways

A9HPGD06

⚠ Discontinued on: 09-Oct-2021

⚠ End-of-service on: 30-Jun-2022

⚠ Discontinued

Main

| | |
|---------------------------|--|
| Range | Acti9 |
| Product name | Phase Segregated |
| Product or component type | Consumer unit |
| Device application | Distribution |
| Enclosure type | Compartmentalised |
| Colour | White (RAL 9003) |
| Provided equipment | Removable gland plates Removable centre plates Removable frame Grounding bar Neutral bar Busbar |

Complementary

| | |
|-------------------------------|---|
| Enclosure mounting | Surface Flush |
| Protection device type | Main incomer: isolator - 4P Main incomer: miniature circuit breaker (MCB) - 4P Main incomer: molded case circuit breaker (MCCB) - 3P or 4P Sub feeder: residual current circuit breaker (RCCB) - 2P (phase) Sub feeder: residual current circuit breaker with overcurrent protection (RCBO) - 2P (phase) Outgoer: miniature circuit breaker (MCB) - 1P |
| [In] rated current | 100 A |
| Total number of 18 mm modules | 38 |
| Number of ways | 6 ways |
| Enclosure/cubicle description | Double door enclosure |
| Enclosure material | Galvanized steel box Galvanized steel DIN rail Galvanized steel cable gland plate CRCA door CRCA central plate |
| Door opening side | Reversible |
| Height | External: 588 mm |
| Width | External: 640 mm |
| Depth | External : 97.41 mm |

Environment

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|-------------------------|---------------------------------------|
| IP degree of protection | IP43 |
| IK degree of protection | IK09 |
| Standards | IS 8623-1 IS 8623-3 IEC 61439-3 |
| Product certifications | ERDA CPRI |

Packing Units

| | |
|------------------------------|----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 15 cm |
| Package 1 Width | 48.5 cm |
| Package 1 Length | 50.2 cm |
| Package 1 Weight | 20.66 kg |

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[How this information helps you](#) >

Use Better



Materials and Substances

EU RoHS Directive

Compliant with Exemptions

China RoHS Regulation

[China RoHS declaration](#)