

# Acti 9 - auxiliary contact OFS 1 O/C for RCCB

A9N26923

### Main

| range of product            | Acti9                              |  |  |
|-----------------------------|------------------------------------|--|--|
| Product or component type   | OC contact                         |  |  |
| Device short name           | OFS                                |  |  |
| Signal contacts composition | 1 C/O                              |  |  |
| [In] rated current          | AC-12 3 A at 380415 V, AC 50/60 Hz |  |  |
|                             | AC-12 6 A at 220240 V, AC 50/60 Hz |  |  |
|                             | DC-12 1 A at 130 V, DC             |  |  |
|                             | DC-12 1.5 A at 60 V, DC            |  |  |
|                             | DC-12 2 A at 48 V, DC              |  |  |
|                             | DC-12 6 A at 24 V, DC              |  |  |
| 9 mm pitches                | 1                                  |  |  |
| Standards                   | EN/IEC 60947-5-1                   |  |  |

## Complementary

| Mounting mode                                    | Fixed  |  |
|--|--|--|
| Mounting support                                 | DIN rail   |  |
| Comb busbar and distribution block compatibility | Top: YES   |  |
| Height   | 85.3 mm  |  |
| width  | 9 mm   |  |
| Depth  | 78.5 mm  |  |
| Net weight                                       | 33 g   |  |
| Colour   | White  |  |
| Connections - terminals                          | Clamp terminal (bottom) 2 cable(s) 1.5 mm² - flexible Clamp terminal (bottom) 1 cable(s) 0.52.5 mm² - rigid Clamp terminal (bottom) 2 cable(s) 1.5 mm² - flexible with ferrule |  |
| Wire stripping length                            | 9 mm   |  |
| Tightening torque                                | 1 N.m  |  |

### **Environment**

| IP degree of protection               | IP20 conforming to EN/IEC 60947-5-1 |  |
|---------------------------------------|-------------------------------------|--|
| Pollution degree                      | 3 conforming to EN/IEC 60947-5-1    |  |
| Tropicalisation                       | 2 conforming to EN/IEC 60947-5-1    |  |
| Relative humidity                     | 0.95 % at 55 °C                     |  |
| Ambient air temperature for operation | -3570 °C                            |  |
| Ambient air temperature for storage   | -4085 °C                            |  |

# **Packing Units**

| Unit Type of Package 1       | PCE       |
|------------------------------|-----------|
| Number of Units in Package 1 | 1         |
| Package 1 Height             | 2.000 cm  |
| Package 1 Width              | 7.800 cm  |
| Package 1 Length             | 9.300 cm  |
| Package 1 Weight             | 44.000 g  |
| Unit Type of Package 2       | BB1       |
| Number of Units in Package 2 | 12        |
| Package 2 Height             | 9.200 cm  |
| Package 2 Width              | 10.000 cm |
| Package 2 Length             | 25.500 cm |
| Package 2 Weight             | 590.000 g |
| Unit Type of Package 3       | S03       |
| Number of Units in Package 3 | 108       |
| Package 3 Height             | 30.000 cm |
| Package 3 Width              | 30.000 cm |
| Package 3 Length             | 40.000 cm |
| Package 3 Weight             | 5.688 kg  |

## **Contractual warranty**

Warranty 18 months

# **Environmental Data**

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

How this information helps you >

#### **Use Better**

| Packaging made with recycled cardboard | No                                       |
|--|--|
| Packaging without single use plastic   | Yes                                      |
| EU RoHS Directive                      | Compliant                                |
| SCIP Number                            | 28bfb466-<br>f950-4025-8655-16cfe4e6c6f3 |
| REACh Regulation                       | REACh Declaration                        |
| China RoHS Regulation                  | China RoHS declaration                   |

## **Use Again**

| ○ Repack and remanufacture |   |
|----------------------------|---|
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Take-back                  | No  |