Product datasheet

Specifications



Socket-outlet, ZENcelo, 2P +E, with shutter, 6A, white

IN8426UNS

Main

Range	ZENcelo
Product or component type	Socket-outlet
Outlet poles configuration	2P + E with shutter
Load type	Resistive
Rated current	6 A
Colour tint	White
Number of modules	2 modules

Complementary

Device presentation	Mechanism
Device mounting	Flush
Material	PA6 base Brass earth contact Nylon + 35 % GF shutter
[Ue] rated operational voltage	250 V
Connections - terminals	Screw terminal
Fixing mode	Snap-fitted
Network type	AC
Network frequency	50/60 Hz
width	47.6 mm
Height	58 mm
Depth	32 mm
Resistance to chemical agents	Not resistant to alcohols Not resistant to cleaning agent Not resistant to thinner

Environment

Ambient air temperature for operation	-535 °C
Relative humidity	095 %
Environmental characteristic	No UV resistant Indoor use
Operating altitude	2000 m
Standards	IS 1293
IP degree of protection	IP20

Packing Units

-	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.2 cm
Package 1 Width	10.2 cm
Package 1 Length	12.5 cm
Package 1 Weight	33.0 g
Unit Type of Package 2	CAR
Number of Units in Package 2	10
Package 2 Height	5.5 cm
Package 2 Width	10.5 cm
Package 2 Length	22.5 cm
Package 2 Weight	380.0 g

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

How this information helps you >

otal Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	1
Environmental Disclosure	Product Environmental Profile

Use Better

S Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Νο
EU RoHS Directive	Compliant
China RoHS Regulation	China RoHS declaration

Use Again

\bigcirc Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	Νο