Product datasheet

Specifications



TVS 3P LC1E40~65 COIL 220V AC 50/60Hz

LAEX3M7

Main

Range	Easy TeSys	
Range of product	Easy TeSys Control	
Product or component type	Contactor coil	
Device short name	LAEX	
Product compatibility	LC1E40E65	
Control circuit type	AC at 50/60 Hz standard	
[Uc] control circuit voltage	220 V AC 50/60 Hz	
Average resistance	153.9 Ohm at 20 °C	
Inductance of closed circuit	8.64 H	

Complementary

Control circuit voltage limits	Operational: 0.851.1 Uc at 50/60 Hz (at <60 °C)	
Inrush power in VA	160 VA 50 Hz cos phi 0.75 (at 20 °C) 140 VA 60 Hz cos phi 0.75 (at 20 °C)	
Hold-in power consumption in VA	Sonsumption in VA 15 VA 50 Hz cos phi 0.3 (at 20 °C) 13 VA 60 Hz cos phi 0.3 (at 20 °C)	

Environment

Ambient air temperature for operation	-560 °C
Net weight	0.11 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.5 cm
Package 1 Width	8.2 cm
Package 1 Length	11.4 cm
Package 1 Weight	98.2 g

Contractual warranty

Warranty

18 months

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

How this information helps you >

\bigtriangledown Environmental footprint	
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Νο
EU RoHS Directive	Compliant with Exemptions
REACh Regulation	REACh Declaration
China RoHS Regulation	China RoHS declaration

Use Again

\circlearrowright Repack and remanufacture	
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Take-back	Νο