

# MPP - gas heavy duty capacitor 3PH 15kVar 440V 50 Hz

MEHVCGSF150A44

#### Main

Range of product	PowerLogic
Product or component type	Gas heavy duty capacitor
Device application	PFC equipment assembly

### Complementary

Reactive power rating	15 kvar
Rated voltage	440 V
[In] rated current	19.4 A
Network frequency	50 Hz
Capacitance tolerance	- 5 % to 10 %
[Imp] maximum permanent current	1.8 x ls
Inrush current	Up to 250 x In
Service life in hours	130000 h
Impregnation material	Bio-degradable dry resin Inert gas impregnated
Operating altitude	4000 m
Safety function	Self healing Pressure sensitive disconnector for every phase Discharge device
Fixing mode	Threaded M12 stud at bottom
Diameter	90 mm
Height	242 mm
Net weight	1.6 kg

#### **Environment**

Standards	IS 13340-1993 IEC 60831-1/2 IS 13341-1992
IP degree of protection	IP20
Relative humidity	095 %

## **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Package 1 Height	30.0 cm
Package 1 Width	13.0 cm
Package 1 Length	13.0 cm
Package 1 Weight	1.92 kg
Unit Type of Package 2	S04
Number of Units in Package 2	15
Package 2 Height	30.0 cm
Package 2 Width	40.0 cm
Package 2 Length	60.0 cm
Package 2 Weight	28.8 kg

## **Environmental Data**

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

How this information helps you >

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	34
Environmental Disclosure	Product Environmental Profile

#### **Use Better**

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant
China RoHS Regulation	China RoHS declaration
☼ Energy efficiency	
Product contributes to saved and avoided emissions	Yes

## **Use Again**

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	No