

Bell press switch, Livia, 10A, 1 module, with indicator, IP2X, white

P1085

Main

Range	Livia
Device application	Doorbell
Product or component type	Switch
Number of rocker	1
Switch function	Bell push switch
Colour tint	White (RAL 9003)
Number of modules	1
Targeted channel	Do it yourself

Complementary

Technology type	Electromechanical
Device mounting	Flush
Actuator	Rocker
Rated current	10 A at 240 V AC 50 Hz
Switch application	Bell
Local signalling	LED indicator (orange)
Material	PC
Surface treatment	Antibacterial
Surface finish	Glossy
Connections - terminals	Screw terminals
Number of terminals	2
Embedding depth	24.1 mm
width	22.7 mm
Height	54.4 mm
Fixing mode	Snap-fitted
Marking	Bell
Depth	35.5 mm
Net weight	19.2 g
IP degree of protection	IP20

Environment

Ambient air temperature for operation	-535 °C
Ambient air temperature for storage	-535 °C
Relative humidity	1095 %
Standards	IS 3854

Environmental

Environmental characteristic Indoor use

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.3 cm
Package 1 Width	6.7 cm
Package 1 Length	11.5 cm
Package 1 Weight	20 g

Contractual warranty

Warranty 18 months

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

How this information helps you >

⊘ Environmental footprint	
Environmental Disclosure	Product Environmental Profile

Use Better

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
REACh Regulation	REACh Declaration
China RoHS Regulation	China RoHS declaration

Use Again

○ Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No