Product datasheet

Specifications



PratiKa wander plug - straight - 16 A - 3P + N + E - 380...415 V AC - IP67

PKE16M735

Main

| Range | Mureva |
|---------------------------|-------------|
| Product or component type | Wander plug |
| Device short name | Mureva plug |
| Plug, socket category | Low voltage |
| Poles description | 3P + N + E |
| Network type | AC |
| Outlet standard | Industrial |

Complementary

| Plug, socket, control station shape | Straight |
|-------------------------------------|---|
| [In] rated current | 16 A |
| [Ue] rated operational voltage | 380415 V |
| Network frequency | 50/60 Hz |
| Ground lug clockwise position | 6 h |
| Plug, socket material | Housing: self-extinguishing engineering polymer |
| Contacts material | Sleeves: brass |
| Connections - terminals | Captive screws |
| Cable cross section | 14 mm ² |
| Cable outer diameter | 815 mm |
| Cable entry | Cable gland Fair lead |
| Thread type | Pg 21 |
| Net weight | 0.21 kg |
| Height | 142 mm |
| width | 89 mm |
| Depth | 89 mm |
| Colour | Grey (RAL 7035) |
| Voltage colour | Red |
| | |

Environment

Standards

IEC 60309-2 IEC 60309-1

| IP degree of protection | IP67 conforming to IEC 60529 | |
|---------------------------------------|---|--|
| IK degree of protection | IK08 conforming to EN 62262 | |
| Fire resistance | 850 °C conforming to IEC 60695-2-11 | |
| Relative humidity | 50 % at 40 °C 70 % at 30 °C 90 % at 20 °C | |
| Operating altitude | 2000 m | |
| Ambient air temperature for operation | 35 °C(86400 s) -25…40 °C | |

Packing Units

| • | |
|------------------------------|----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 8.7 cm |
| Package 1 Width | 8.8 cm |
| Package 1 Length | 15.6 cm |
| Package 1 Weight | 222.0 g |
| Unit Type of Package 2 | BB1 |
| Number of Units in Package 2 | 10 |
| Package 2 Height | 17.8 cm |
| Package 2 Width | 26.6 cm |
| Package 2 Length | 27.0 cm |
| Package 2 Weight | 2.398 kg |
| Unit Type of Package 3 | S03 |
| Number of Units in Package 3 | 20 |
| Package 3 Height | 30.0 cm |
| Package 3 Width | 30.0 cm |
| Package 3 Length | 40.0 cm |
| Package 3 Weight | 5.283 kg |
| | |

Contractual warranty

Warranty

18 months

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

How this information helps you >

| earrow ear | |
|---|-------------------------------|
| Carbon footprint (kg.eq.CO2 per CR, Total Life cycle) | 6 |
| Environmental Disclosure | Product Environmental Profile |

Use Better

| S Materials and Substances | | |
|--|--|--|
| Packaging made with recycled cardboard | Yes | |
| Packaging without single use plastic | Yes | |
| EU RoHS Directive | Compliant with Exemptions | |
| SCIP Number | 661ec80b- b956-4b0a-92bb-53046f4cfb4c | |
| REACh Regulation | REACh Declaration | |
| China RoHS Regulation | China RoHS declaration | |

Use Again

| \bigcirc Repack and remanufacture | |
|-------------------------------------|--|
| Circularity Profile | No need of specific recycling operations |
| Take-back | No |

Technical Illustration

Exploded view

