

PratiKa wander plug - straight - 32 A - 3P + N + E - 380...415 V AC - IP67

PKE32M735

Main

Range	Mureva
Product or component type	Wander plug
Device short name	Mureva plug
Plug, socket category	Low voltage
Poles description	3P + N + E
Network type	AC
Outlet standard	Industrial

Complementary

Plug, socket, control station shape	Straight
[In] rated current	32 A
[Ue] rated operational voltage	380415 V
Network frequency	50/60 Hz
Ground lug clockwise position	6 h
Plug, socket material	Housing: self-extinguishing engineering polymer
Contacts material	Sleeves: brass
Connections - terminals	Captive screws
Cable cross section	2.510 mm²
Cable outer diameter	11.521 mm
Cable entry	Cable gland Fair lead
Thread type	Pg 21
Net weight	0.25 kg
Height	160 mm
width	102 mm
Depth	102 mm
Colour	Grey (RAL 7035)
Voltage colour	Red

Environment

Standards	IEC 60309-1	
	IEC 60309-2	

IP degree of protection	IP67 conforming to IEC 60529	
IK degree of protection	IK08 conforming to EN 62262	
Fire resistance	850 °C conforming to IEC 60695-2-11	
Relative humidity	50 % at 40 °C 70 % at 30 °C 90 % at 20 °C	
Operating altitude	2000 m	
Ambient air temperature for operation	35 °C (86400 s) -2540 °C	

Packing Units

_	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10.500 cm
Package 1 Width	10.500 cm
Package 1 Length	17.000 cm
Package 1 Weight	307.000 g
Unit Type of Package 2	BB1
Number of Units in Package 2	6
Package 2 Height	17.000 cm
Package 2 Width	26.000 cm
Package 2 Length	27.000 cm
Package 2 Weight	2.030 kg
Unit Type of Package 3	S03
Number of Units in Package 3	12
Package 3 Height	30.000 cm
Package 3 Width	30.000 cm
Package 3 Length	40.000 cm
Package 3 Weight	4.512 kg

Contractual warranty

Warranty 18 months

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

How this information helps you >

⊘ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	18
Environmental Disclosure	Product Environmental Profile

Use Better

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant with Exemptions
SCIP Number	661ec80b- b956-4b0a-92bb-53046f4cfb4c
REACh Regulation	REACh Declaration
China RoHS Regulation	China RoHS declaration

Use Again

○ Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No