

Switch, Unica Pure, with indicator, 1-pole 1-way, 16AX, 1 module, pillar terminals, grey

UNS161SWL1M_GY

Main

Range	Unica Pure
Product or component type	Switch
Device presentation	Mechanism
Technology type	Electromechanical
Colour tint	Grey (RAL 7016)

Complementary

Device mounting	Flush
Number of rocker	1
Number of modules	1 module
Control type	Rocker
Switch function	1-pole 1-way
Rated current	16 AX
[Ue] rated operational voltage	240 V
Network type	AC
Network frequency	50 Hz
Local signalling	Neon
Material	PC: front cover PA6: back cover
Connections - terminals	Pillar terminals
width	22.5 mm
Height	45 mm
Depth	47.2 mm

Environment

Ambient air temperature for operation	-535 °C
Relative humidity	1095 %
Environmental characteristic	Indoor use
Standards	IS 3854
IP degree of protection	IP20

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.72 cm
Package 1 Width	4.5 cm
Package 1 Length	2.25 cm
Package 1 Weight	25 g
Unit Type of Package 2	BB1
Number of Units in Package 2	20
Package 2 Height	10.5 cm
Package 2 Width	7.5 cm
Package 2 Length	24 cm
Package 2 Weight	500 g

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

How this information helps you >

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	8
Environmental Disclosure	Product Environmental Profile

Use Better

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACh Regulation	REACh Declaration
China RoHS Regulation	China RoHS declaration

Use Again

Control Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No

Image of product / Alternate images

Alternative















09-Jan-2025