

Socket-outlet, Unica Pure, mechanism, 2P + E, 6A, with shutter grey

UNS6SK3P2MNS_GY

Main

Range	Unica Pure
Product or component type	Socket-outlet
Device presentation	Mechanism
Number of modules	2 modules
Socket number	1
Colour tint	Grey (RAL 7016)

Complementary

Device mounting	Flush	
Outlet poles configuration	2P + E	
Cover type	With shutter	
Rated current	6 A	
[Ue] rated operational voltage	250 V	
Network type	AC	
Network frequency	50/60 Hz	
Material	PC front cover PA6 back cover	
Connections - terminals	Screw terminal	
Fixing mode	Snap-fitted	
width	45 mm	
Height	45 mm	
Depth	32 mm	
Resistance to chemical agents	Not resistant to alcohols Not resistant to cleaning agent Not resistant to thinner	

Environment

Ambient air temperature for	-535 °C
operation	
Relative humidity	1095 %
Standards	IS 1293
IP degree of protection	IP20

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.16 cm
Package 1 Width	10.5 cm
Package 1 Length	13.5 cm
Package 1 Weight	32 g
Unit Type of Package 2	CAR
Number of Units in Package 2	10
Package 2 Height	5.5 cm
Package 2 Width	10 cm
Package 2 Length	23.5 cm
Package 2 Weight	369 g
Unit Type of Package 3	BB1
Number of Units in Package 3	120
Package 3 Height	24.5 cm
Package 3 Width	26 cm
Package 3 Length	33 cm
Package 3 Weight	4.64 kg

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

How this information helps you >

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	1
Environmental Disclosure	Product Environmental Profile

Use Better

No
No
Compliant
REACh Declaration
China RoHS declaration

Use Again

○ Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No

Image of product / Alternate images

Alternative













