Product datasheet

Specifications



TeSys VARIO - additional neutral block - 40 A - for V02...V2

VZ11

Main

TeSys
VZ
Additional neutral block
High performance
1N
1 NO
Early make, late break
V1
V2
V02
V0
V01
TeSys TeSys VARIO switch disconnector
AC
DC
50/60 Hz

Complementary

Mounting location	Left Right
[Ue] rated operational voltage	690 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	6 kV
[Ith] conventional free air thermal current	40 A
Mechanical durability	100000 cycles
Electrical durability	30000 cycles DC-15 100000 cycles AC-21
Connections - terminals	Screw clamp terminals6 mm² - flexible - with cable end Screw clamp terminals10 mm² - solid
Tightening torque	2.1 N.m - on screw clamp terminals
Height	74 mm
width	16 mm
Depth	35 mm
Net weight	0.05 kg

Environment

Standards	IEC 60947-3
Product certifications	GL CSA UL UKCA
Protective treatment	TC
IP degree of protection	IP20 conforming to IEC 60529
Mechanical robustness	Vibrations 10150 Hz (1 gn) conforming to IEC 60068-2-6 Shocks 11 ms (15 gn) conforming to IEC 60068-2-27
Ambient air temperature for operation	-2050 °C
Fire resistance	960 °C conforming to IEC 60695-2-1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.500 cm
Package 1 Width	3.700 cm
Package 1 Length	9.000 cm
Package 1 Weight	46.000 g
Unit Type of Package 2	S02
Number of Units in Package 2	69
Package 2 Height	15.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	3.582 kg

Contractual warranty

Warranty

18 months

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

How this information helps you >

earrow earrow earrow earr	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	2
Environmental Disclosure	Product Environmental Profile

Use Better

S Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Νο
EU RoHS Directive	Compliant with Exemptions
SCIP Number	65661eb0-9ea7-4d52- b0a4-16b981f28f63
REACh Regulation	REACh Declaration
China RoHS Regulation	China RoHS declaration
PVC free	Yes

Use Again

\circlearrowright Repack and remanufacture	
Circularity Profile	No need of specific recycling operations

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen free product
Νο

Technical Illustration

Assembly's dimensions

