

Opale bell press switch 1-way 6 A white

X1005WH

Main

Range	Opale
Product or component type	Bell press switch
Device presentation	Mechanism
Quantity per set	Set of 10
Colour tint	White

Complementary

Technology type	Electromechanical
Device mounting	Flush
Number of modules	1 module
Actuator	Rocker
Switch function	1-way
Rated current	6 A
[Ue] rated operational voltage	250 V
Network type	AC
Surface finish	Satin
Network frequency	50 Hz
Fixing mode	By captive screws
Connections - terminals	Shrouded terminals
Material	ABS + PC: front cover PC: base cover
Height	48 mm
width	21 mm
Depth	36.9 mm

Environment

Standards	IS 3854:1997/A1
IP degree of protection	IP20
Ambient air temperature for operation	-535 °C
Relative humidity	1095 %
Environmental characteristic	Indoor use

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.2 cm
Package 1 Width	2.1 cm
Package 1 Length	3.3 cm
Package 1 Weight	15 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	5 cm
Package 2 Width	10 cm
Package 2 Length	12 cm
Package 2 Weight	222.2 g
Unit Type of Package 3	CAR
Number of Units in Package 3	20
Package 3 Height	6.3 cm
Package 3 Width	10.8 cm
Package 3 Length	23.3 cm
Package 3 Weight	305 g

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

How this information helps you >

⊘ Environmental footprint	
Environmental Disclosure	Product Environmental Profile

Use Better

Packaging made with recycled cardboard	Yes	
Packaging without single use plastic	No	
EU RoHS Directive	Compliant	
REACh Regulation	REACh Declaration	
China RoHS Regulation	China RoHS declaration	

Use Again

○ Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No