

# Opale socket-outlet 3P with shutters 6 A white

X2106WH

#### Main

Range	Opale
Product or component type	Socket-outlet
Device presentation	Mechanism
Outlet poles configuration	3P with shutters
Colour tint	White
[Ue] rated operational voltage	250 V
Network type	AC
Network frequency	50/60 Hz

## Complementary

Number of power socket outlets	1	
Device mounting	Flush	
Number of modules	2 modules	
Rated current	6/16 A	
Connections - terminals	Shrouded terminals	
Surface finish	Satin	
Fixing mode	Snap-fitted	
Material	PC: front cover PA (polyamide) 6: base cover	
Height	51 mm	
width	42.25 mm	
Depth	30.2 mm	
Resistance to chemical agents	Not resistant to alcohols Not resistant to cleaning agent Not resistant to thinner	

#### **Environment**

Environmental characteristic	Flame retardant
Standards	IS 1293
IP degree of protection	IP20
Ambient air temperature for operation	-535 °C
Relative humidity	1095 %

## **Packing Units**

•	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.1 cm
Package 1 Width	4.2 cm
Package 1 Length	2.1 cm
Package 1 Weight	34 g
Unit Type of Package 2	BB1
Number of Units in Package 2	280
Package 2 Height	215 cm
Package 2 Width	340 cm
Package 2 Length	445 cm
Package 2 Weight	9525 g

## **Environmental Data**

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

How this information helps you >

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	1
Environmental Disclosure	Product Environmental Profile

#### **Use Better**

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
REACh Regulation	REACh Declaration
China RoHS Regulation	China RoHS declaration

### **Use Again**

Circularity Profile	No need of specific recycling operations
Take-back	No