# **Product datasheet**

Specifications



### ① Discontinued

# Main

Range	Opale
Product or component type	Telephone socket
Device presentation	Complete product
Cable shielding type	UTP
Data socket type	RJ11
Colour tint	White
Type of packing	Flow-pack
Quantity per set	10
Colour tint	White

RJ11 TEL. OUTLET FOR ALPHA

**NO SHUTTERE White** 

() Discontinued on: 13-Sept-2024

X4010WH

### Complementary

Device mounting	Flush
Socket number	1
Communication network category	6
Connections - terminals	IDC
Cable stiffness	Rigid
Material	ABS + PC: front cover PA6: base cover
Fixing mode	Claws
Height	48 mm
width	21 mm
Depth	18 mm
Environmental characteristic	Acetone Window-cleaning fluid Liquid soap Bleach Oil Alcohol Petrol

# Environment

IP degree of protection	IP20
IK degree of protection	IK01
Ambient air temperature for storage	035 °C

Ambient air temperature for	1530 °C
operation	

# **Packing Units**

•	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.5 cm
Package 1 Width	0.55 cm
Package 1 Length	1 cm
Package 1 Weight	9.65 g

# C Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### How this information helps you >

earrow  earrow earrow  earr	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	1
Environmental Disclosure	Product Environmental Profile

# **Use Better**

S Materials and Substances	
EU RoHS Directive	Compliant
China RoHS Regulation	China RoHS declaration

# **Use Again**

$\circlearrowright$ Repack and remanufacture	
Circularity Profile	No need of specific recycling

operations