

# Product datasheet

Specifications



## RJ11 TEL. OUTLET FOR OPALE SHUTTERED White

X4011WH

### Main

Range	Opale
Product or component type	Telephone socket
Device presentation	Complete product
Cable shielding type	UTP
Data socket type	RJ11
Colour tint	White
Type of packing	Flow-pack
Quantity per set	10
Colour tint	White

### Complementary

Device mounting	Flush
Socket number	1
Communication network category	6
Connections - terminals	IDC
Cable stiffness	Rigid
Material	ABS + PC: front cover PA6: base cover
Fixing mode	Claws
Height	48 mm
width	21 mm
Depth	18 mm
Environmental characteristic	Acetone Window-cleaning fluid Liquid soap Bleach Oil Alcohol Petrol

### Environment

IP degree of protection	IP20
IK degree of protection	IK01
Ambient air temperature for storage	0...35 °C
Ambient air temperature for operation	15...30 °C

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2 cm
Package 1 Width	2.5 cm
Package 1 Length	5.5 cm
Package 1 Weight	14 g

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[How this information helps you >](#)

### Environmental footprint

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	1
---	---

Environmental Disclosure

[Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard	Yes
--	-----

Packaging without single use plastic	No
--------------------------------------	----

<a href="#">EU RoHS Directive</a>	Compliant
-----------------------------------	-----------

China RoHS Regulation	<a href="#">China RoHS declaration</a>
-----------------------	--

## Use Again

### Repack and remanufacture

Circularity Profile	No need of specific recycling operations
---------------------	--

Take-back	No
-----------	----