

Product datasheet

Specifications



TV SOCKET White

X4500WH

Main

Range	Opale
Product or component type	TV socket
Device presentation	Complete product
Cable shielding type	UTP
Data socket type	BNC coaxial
Colour tint	Coke grey
Type of packing	Flow-pack
Quantity per set	10

Complementary

Device mounting	Flush
Socket number	1
Communication network category	6
Connections - terminals	IDC
Cable stiffness	Rigid
Material	PC: front cover
Path attenuation	TV: 1.5 dB
Fixing mode	Claws
Height	48 mm
width	21 mm
Depth	15.8 mm
Colour tint	White
Standards	CE
TV connector	Male IEC 9.52 mm
Number of modules	1

Environment

IP degree of protection	IP20
IK degree of protection	IK01

Resistance to chemical agents	Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner Resistant to hydrogen peroxide 10 volumes Resistant to hexane
Ambient air temperature for storage	-25...55 °C
Ambient air temperature for operation	-25...55 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.5 cm
Package 1 Width	2.5 cm
Package 1 Length	5.5 cm
Package 1 Weight	13.8 g

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[How this information helps you >](#)

Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard **Yes**

Packaging without single use plastic **No**

[EU RoHS Directive](#) **Compliant**

China RoHS Regulation [China RoHS declaration](#)

Use Again

Repack and remanufacture

Circularity Profile **No need of specific recycling operations**

Take-back **No**