

# Product datasheet

Specifications



## USB charger, Opale, 2.1 A, 2 module, White

X7003WH

### Main

Range	Opale
Product or component type	USB charger
Device application	Power supply
Type of USB power supply	USB type A + A
Device presentation	Mechanism
Colour tint	White
Type of packing	Bulk
Quantity per set	5
Number of terminals	2 pillar terminal
[Ue] rated operational voltage	100...240 V
Network type	AC
Network frequency	50...60 Hz

### Complementary

Socket number	2
Device mounting	Flush
Surface finish	Glossy
Number of modules	2 modules
Fixing mode	Clipped
Output voltage	5 V DC, 2.1 A
Integrated connection type	2 2 USB ports
Material	PC
Height	44.5 mm
width	51 mm
Depth	38.4 mm
Standards	IEC 60950-1 IS 13252

### Environment

Ambient air temperature for storage	-5...35 °C
Relative humidity	10...95 %
Ambient air temperature for operation	-10...45 °C

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.8 cm
Package 1 Width	4.5 cm
Package 1 Length	5.1 cm
Package 1 Weight	52 g
Unit Type of Package 2	BB1
Number of Units in Package 2	75
Package 2 Height	245 cm
Package 2 Width	260 cm
Package 2 Length	330 cm
Package 2 Weight	5367 g

# Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[How this information helps you >](#)

## Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard **Yes**

Packaging without single use plastic **No**

[EU RoHS Directive](#) **Compliant**

REACH Regulation [REACH Declaration](#)

China RoHS Regulation [China RoHS declaration](#)

## Use Again

### Repack and remanufacture

Circularity Profile **No need of specific recycling operations**

Take-back **No**